

DIRECTIONS FOR USE

Turf (all grasses)

Apply 8 lbs of 8-2-2 per 1,000 sq ft of turf area (1/2 lb of nitrogen per 1,000 sq ft), 2-4 times a year or as needed.

For best results, adequate irrigation should be practiced after application and throughout the growing season.

For newly seeded areas and establishment apply 10-15 lbs / 1,000 sq ft. For repair of damaged turf apply 10-16 lbs / 1,000 sq ft.

Do not apply near water, storm drains, or drainage ditches. Do not apply if heavy rains are expected. Apply this product only to your lawn/garden, and sweep any product that lands on driveways or sidewalks or streets back onto your lawn/garden.

Manufactured for:
EarthWorks™
 30 Morgan Hill Rd.
 Easton, PA 18042 USA
 www.soilfirst.com
 800-732-TURF

F1399

STANDARD GRADE

8-2-2
 Replenish

Guaranteed Analysis

Total Nitrogen (N)..... 8.00%
 6.30% Ammoniacal Nitrogen
 1.50% Water Insoluble Nitrogen
 0.20% Water Soluble Nitrogen

Available Phosphate (P₂O₅) 2.00%
 Soluble Potash (K₂O) 2.00%
 Sulfur (S) 7.00%
 7.00% Combined Sulfur (S)

Derived from:
 Composted poultry manure
 and ammonium sulfate.

Also Contains Non-Plant Food Ingredients

75% Organic matter (derived from
 composted poultry manure,
 contains carbon)
 25% Total Other Ingredients

Organic matter in the composted poultry manure is a source of carbon that serves as food for soil microbes

Information regarding the contents and levels of metals in this product is available at :
<http://www.aapfco.org/metals.htm>

**Suggested Spreader Settings
 8-2-2 Standard Grade**

Spreader	Spread Width	Nitrogen in lb/1000 sq ft	
		0.5	1.0
Vicon	28'	32	49
Lely	25'	5.75	8
AccuPro 2000 (cone 8)	9'	R	V
Scott's R8-A (cone 8)	10'	L.5	O
Lesco	10'	19,H.5	24,K

These settings were calibrated and field tested. Age, condition of spreader, speed of operator and evenness of terrain may require adjustment of setting for desired coverage.

- Vicon spreader settings are based on 540 rpm and a ground speed of 4.7 mph.
- Lely spreader settings are based on 425 rpm and a ground speed of 4.7 mph.

EarthWorks™
STANDARD GRADE
8-2-2
 Replenish

Pull narrow tape to open

EarthWorks™

CARBON BASED FERTILITY

Leading the way since 1988



Replenish

8-2-2

STANDARD GRADE

**Covers 8,000 square feet
 at 1/2 lb Nitrogen per 1000 sq ft**

Prilled

**Net Weight: 50 pounds
 22.68 Kilograms**

Replenish
EarthWorks™
STANDARD GRADE
8-2-2

242361 E-194-013 8-13
 FREIGHT SHIPPING BAG
 MEETING REQUIREMENTS OF
 APPLICABLE FREIGHT CLASSIFICATION
 GUARANTEED BY
 BAN CRO FT BAG, INC.
 WEST MONROE, LOUISIANA