



= World Headquarters=

MATERIAL SAFETY DATA SHEET M.S.D.S.

I - PRODUCT IDENTIFICATION

TRADE NAME (as labeled)

: SEA GROW - 4 -26-26

MANUFACTURER'S NAME

: GROW MORE, INC.

15600 New Century Drive

Gardena, CA 90248 Tel. (310) 515-1700 Fax (310) 515-4937

DATE PREPARED/REVISED

March 20, 2000

NAME OF PREPARER

H. Langheim

II – HAZARDOUS INGREDIENTS

Exposure Limits in Air (give units)

Chemical Name

CAS No. & %

ACGH TLV

OSHA PEL OTHER (specify)

Sodium Molybdate

7439987

5 mg/m3

5 mg/m3

Manganese EDTA

7439965

Oral LD50Rat: 1750 mg/kg

Copper EDTA 7440508

Zinc EDTA

7440666

III- PHYSICAL PROPERTIES

VAPOR DENSITY (AIR = 1)

: N/A

SPECIFIC GRAVITY

: Approx. 1.7 g/cc

SOLUBILITY IN WATER

: 300 g/1 or greater

VAPOR PRESSURE, mmHg AT 20°C

: N/A

APPEARANCE AND ODOR

: Fine crystals & powder

MELTING POINT OR RANGE, °F

: Not established

BOILING POINT OR RANGE, °F

: N/A

EVAPORATION RATE (BUTYLACETATE = 1)

: 0

DECOMPOSITION TEMPERATURE:

: 250 - 374°F

pH 1% SOLUTION

: 4.5 - 5.5

MOLECULAR WEIGHT

: 110 - 117

GROW MORE

MSDS for Sea Grow – 4-26-26 (con	tinuation) Page No. 2				
CHEMICAL NAME	: Proprietary mixture containing Ammonium Phosphate, Potassium Phosphate, Potassium Nitrate, Potassium Sulfate, Ammonium Sulfate, Ammonium Nitrate, Urea and Micronutrients				
IV – FIRE AND EXPLOSION					
FLASH POINT. °F (Give Method) AUTO IGNITION TEMPERATURE ° FLAMMABLE LIMITS IN AIR (Vol.9)					
FIRE EXTINGUISHING MATERIAL water spray foam	carbon dioxideotherother				
SPECIAL FIREFIGHTING PROCEDU	JRE: Use abundant amount of water in early stages of fire.				
	ZARDS: When large quantities are involved in fire, solids may fuse or gen Oxides. In such conditions application of water may result in				
V – HEALTH HAZARD INFORMA	TION				
L.D. 50	: Not established.				
SYMPTOMS OF OVEREXPOSURE I	FOR EACH POTENTIAL ROUTE OF EXPOSURE:				
INHALED	: Dust can irritate upper respiratory system.				
CONTACT WITH SKIN OR	EYES : Prolonged skin contact may cause Dermatitis. Dust may irritate eyes.				
ABSORBED THROUGH SK	: Not known adverse effects at this time.				
SWALLOWED	: Nausea, diarrhea, diuresis, muscular debility.				
FIRST AID (EMERGENCY) PRODEI	DURES:				
	: Wash thoroughly with water for at least 15 minutes. Hold eyelids apart during flushing. Send patient immediately to physician.				
SKIN CONTACT : V	: Wash with soap and water.				
INHALED : R	: Remove from exposure. Treat symptomatically.				
Γ	: Rinse mouth. Drink 2-3 glasses of water and seek medical assistance. Do not induce vomiting or give anything by mouth to an unconscious person.				

WISDS for Sea Grow –		(continuation)			rage -3-
SUSPECTED CANCE _X_ No		I T? roduct's ingredien	ts are not found	in the list below	<i>i</i> .
Yes	FEDE	RAL OSHA	NTP	IARC	····
		sing CAL-OSHA l OSHA carcinoge			ster with CAL-OSHA. TI
VI – REACTIVITY D	ATA				*
STABILITY	:	X Stable		Unstable	
CONDITIONS TO AV	OID :		odium Phosphite to tin, solder, tin		th Sodium Hyposulfite tes.
INCOMPATIBILITY Material to avoid)	:	Corrosive to A	luminum, Steel,	Brass, Copper.	
HAZARDOUS DECOM Oxides.	MPOSITI	ON PRODUCTS	(INCLUDING C	COMBUSTION	PRODUCTS): Nitrogen
HAZARDOUS POLYN	/IERIZAT	TION:	_ May occur	XV	Will not occur
CONDITIONS TO AV	OID	: Avoid	l fire.		
	(*)			(**) ***	
VII – SPILL, LEAK &	& DISPO	SAL PROCEDU	RES:		
SPILL RESPONSE PR	OCEDUR	E (Include emplo	yee protection n	neasures):	
Sweep into breaker Drain into the sewe			ter. Add soda as	h. Mix and neu	stralize with 6m HCL.
PREPARINNG WAST	ES FOR I	DISPOSAL (Cont	ainer types, neut	ralization, etc.)	:
					. After 24 hours, decant over with abundant water.